

Uni-7 Series

The Uni-7 line offers its own set of unique features. Starting with the color touchscreen, users can customize their display with their own color photos. Positive input response allows users to feel a tactile sensation and hear a beep when the screen or a button is pressed. Save space and time with a front-loading label cassette. The Uni-7 also operates in several different languages, and provides PC like capabilities to support Intranet store browsing.

Uni-7 Hanging

PRICE-COMPUTING SCALE/PRINTER/
COLOR TOUCHSCREEN

Ishida's Uni-7 is the only color-touchscreen hanging scale on the market. This suspended ergonomic design holds product within a bowl-shaped pan, while keypad and display are kept at eye level away from moisture.

Uni-7 Elevated Keypad

PRICE-COMPUTING SCALE/
PRINTER/COLOR TOUCHSCREEN

The elevated display offers additional ergonomic benefits to many types of work areas. Available with an optional receipt printer and color customer display.



Pictured with optional receipt printer.

Uni-7 Self-Serve

PRICE-COMPUTING SCALE/
PRINTER/COLOR TOUCHSCREEN

Modular product billboards can be arranged to best suit any self-service need. These large easy-to-read displays offer customer convenience in a user-friendly format.



Price Computing Scale with Printer and Touchscreen

Uni-7 Series



Hanging

Elevator
twin printer



Elevator
single printer



Self-service



Pole



Bench



Labeler
printer only

Specifications

Weighing capacity (Dual Range):	0-15 x 0.005lb; 15-30 x 0.010lb
Weighing accuracy:	1/3000
Power supply:	AC100 – 240V, 50/60 Hz
Power consumption:	1.0A/0.5A
Operator display:	7-inch color LCD touch screen with backlight and positive input response
Customer display:	7-inch color LCD with backlight
Keypad:	84 keys (Preset keys)
Printing method:	Direct thermal
Thermal head:	2 inches and 8 dots/mm
Printing speed:	MAX 120mm/sec
Label size:	Width: 1.2in – 2.4in (30mm to 60mm) Length: 0.8in – 5.9in (20mm to 150mm)
Number of cassettes:	7 cassettes (front-loading type)
Roll size:	Outer diameter: 3.9in (100mm) MAX Inner diameter: 1.6in (40mm) MIN
Weight:	Bench type: Approx. 26lbs (11.5kg) Pole type: Approx. 28lbs (12.5kg)
Operating conditions:	Temperature: -5 to 40°C Humidity: 20 to 85% No condensation
Network Interface:	Static TCP/IP 10/100 Base T Ethernet
Warranty:	One-year limited warranty
Approval:	NTEP CC 07-099A1

Options

- Wireless 802.11b/g; WPA - PSK; IEEE 802.11i - PSK with AES-CCMP Encryption; TKIP Encryption; 64/128-bit WEP
- ScaleLink Pro, PLU management software

Your Rice Lake Weighing Systems distributor is:



230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com/retail

An ISO 9001 Registered Company
© 2010 Rice Lake Weighing Systems 05/10
Specifications subject to change without notice.