

# Uni-7 Series

The Uni-7 line offers its own set of unique features. Starting with the color touchscreen, users can customize their display with their own color photos. Positive input response allows users to feel a tactile sensation and hear a beep when the screen or a button is pressed. Save space and time with a front-loading label cassette. The Uni-7 also operates in several different languages, and provides PC like capabilities to support Intranet store browsing.

## Uni-7 Hanging

PRICE-COMPUTING SCALE/PRINTER/  
COLOR TOUCHSCREEN

Ishida's Uni-7 is the only color-touchscreen hanging scale on the market. This suspended ergonomic design holds product within a bowl-shaped pan, while keypad and display are kept at eye level away from moisture.

## Uni-7 Elevated Keypad

PRICE-COMPUTING SCALE/  
PRINTER/COLOR TOUCHSCREEN

The elevated display offers additional ergonomic benefits to many types of work areas. Available with an optional receipt printer and color customer display.



Pictured with optional receipt printer.

## Uni-7 Self-Serve

PRICE-COMPUTING SCALE/  
PRINTER/COLOR TOUCHSCREEN

Modular product billboards can be arranged to best suit any self-service need. These large easy-to-read displays offer customer convenience in a user-friendly format.



Price Computing Scale with Printer and Touchscreen

# Uni-7 Series



Hanging

Elevator  
twin printer



Elevator  
single printer



Self-service



Pole



Bench



Labeler  
printer only

## Specifications

Weighing capacity (Dual Range):	0-15 x 0.005lb; 15-30 x 0.010lb
Weighing accuracy:	1/3000
Power supply:	AC100 – 240V, 50/60 Hz
Power consumption:	1.0A/0.5A
Operator display:	7-inch color LCD touch screen with backlight and positive input response
Customer display:	7-inch color LCD with backlight
Keypad:	84 keys (Preset keys)
Printing method:	Direct thermal
Thermal head:	2 inches and 8 dots/mm
Printing speed:	MAX 120mm/sec
Label size:	Width: 1.2in – 2.4in (30mm to 60mm) Length: 0.8in – 5.9in (20mm to 150mm)
Number of cassettes:	7 cassettes (front-loading type)
Roll size:	Outer diameter: 3.9in (100mm) MAX Inner diameter: 1.6in (40mm) MIN
Weight:	Bench type: Approx. 26lbs (11.5kg) Pole type: Approx. 28lbs (12.5kg)
Operating conditions:	Temperature: -5 to 40°C Humidity: 20 to 85% No condensation
Network Interface:	Static TCP/IP 10/100 Base T Ethernet
Warranty:	One-year limited warranty
Approval:	NTEP CC 07-099A1

## Options

- Wireless 802.11b/g; WPA - PSK; IEEE 802.11i - PSK with AES-CCMP Encryption; TKIP Encryption; 64/128-bit WEP
- ScaleLink Pro, PLU management software

Your Rice Lake Weighing Systems distributor is:



230 W. Coleman St. • Rice Lake, WI 54868 • USA  
TEL: 715-234-9171 • FAX: 715-234-6967 • [www.ricelake.com/retail](http://www.ricelake.com/retail)

An ISO 9001 Registered Company  
© 2010 Rice Lake Weighing Systems 05/10  
Specifications subject to change without notice.