

## Ishida AC-4000/B/ic Price Computing Scale/Printer

**60 lb capacity available!**



### Approvals



PART #	MODEL	CAPACITY
<b>WITH LABEL CASSETTE</b>		
80808.....	AC-4000 .....	15 lb x 0.005 lb/30 lb x 0.01 lb
96897* ...	AC-4000 with RF .....	15 lb x 0.005 lb/30 lb x 0.01 lb
96931.....	AC-4000ic .....	30 lb x 0.01 lb/60 lb x 0.02 lb
Consult* .	AC-4000ic with RF .....	30 lb x 0.01 lb/60 lb x 0.02 lb
<b>NON-LABEL CASSETTE (B VERSION)</b>		
79477.....	AC-4000 .....	15 lb x 0.005 lb/30 lb x 0.01 lb
96898* ...	AC-4000 with RF .....	15 lb x 0.005 lb/30 lb x 0.01 lb
96932.....	AC-4000ic .....	30 lb x 0.01 lb/60 lb x 0.02 lb
Consult* .	AC-4000ic with RF .....	30 lb x 0.01 lb/60 lb x 0.02 lb

Networking capabilities along with user-friendly operation make the AC-4000 series an ideal supermarket scale for bakeries, delis, seafood, meat and produce applications. The AC-4000 communicates via Ethernet or RF wireless transmission and allows quick label changes with front-loading cassettes. Choose from multiple label formats and use the powerful batch printing feature for increased productivity.



Label cassette, AC-4000



AC-4000ic has a 60 lb capacity and is available in cassette or non-cassette versions.

### Applications

- Meat, seafood, deli, produce and bakery departments

### Standard Features

- Dual-range weighing (0-15 lb x 0.005 lb/15-30 lb x 0.01 lb)
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Bright dot matrix display for alphanumeric messaging
- 184 function keys assist with intuitive operation
- Fast printing speed results in greater customer throughput
- Multiple label formats for multi-department support
- Powerful batch printing feature frees operator's time
- Flash ROM for remote update of application software
- Proportional tare
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

### Options/Accessories

- 46915.....Additional label cassette
  - 46916.....Produce platter, 17" W x 11.5" D
  - 46917.....Fish platter, 17" W x 11.5" D
  - 71199.....Polyethylene scale shelf, 18.75" W x 17" D x 1" H
  - 93154.....In-use cover
- COMMUNICATION**
- 65231\*\* .....ScaleLink Pro, product management software
  - 92462.....Internal wireless communication, 802.11b/g
  - 94743.....Symbol® access point 5131, 802.11b/g (complete with two antennas, power injector and power cord)

### LABEL STOCK

Please refer to the Retail Label section of this catalog for ordering information and case quantity pricing.

\*RF is factory installed (includes part no. 92462).

\*\*License file required for operation. Must supply store name and address at time of order. One license required per location.

Symbol® is a registered trademark of Symbol Technologies, Inc.



### ScaleLink Pro

Sophisticated product management made simple

- Import ASCII delimited files for seamless integration and continued operation
- Joins individual scales to in-store computer, POS servers, or central hosting computer networks
- Enter and maintain item data, price changes and more

**CAPACITY/MINIMUM GRADUATION:**

- 15 lb x 0.005 lb/30 lb x 0.01 lb (dual range standard)
- 30 lb x 0.01 lb (single-range available)
- 30 lb x 0.01 lb/60 lb x 0.02 lb (AC-4000ic)

**DISPLAY ITEMS:**

- Tare: 4-digits
- Unit price: 5-digits
- Weight: 5-digits
- Total Price: 6-digits

**DISPLAY:**

- Fluorescent display (Upper)
- Dot matrix display (Lower) (256 x 16 dots)

**PRINTING SPEED:**

- 3.2" (80 mm) per second

**PRESET KEYS:**

- 92 one-touch preset keys
- 184 preset keys (Assign two items per key)

**MEMORY CAPACITY:**

- Standard: 2MB

**LABEL SIZE:**

- Label width: 1.5" - 2.5" (38 mm - 64 mm)

Label length: 1.2" - 9.5" (30 mm - 240 mm)

**COMMUNICATION:**

TCP/IP 10/100 Base T Ethernet

**LABEL ROLL:**

Inside diameter: 1.6" (40mm)  
Outside diameter: 3.9" (100mm)

**WEIGHT:**

24lbs.

**POWER SUPPLY:**

AC100 V / 120 V / 220 V / 240 V, 50/60 Hz

**POWER CONSUMPTION:**

Stand-by 50W  
In operation 100W

**CLASSIFICATION:**

NTEP certified, CC 95-057A6, UL listed

**WARRANTY:**

1-year limited warranty

**DIMENSIONS**

A: 15.8" (400 mm)	H: 4.9" (125 mm)
B: 9.8" (250 mm)	I: 3.2" (80 mm)
C: 2.6" (65 mm)	J: 17.8" (453 mm)
D: 8.9" (225 mm)	K: 6.7" (170 mm)
E: 16.5" (420 mm)	L: 18.4" (466 mm)
F: 6.7" (170 mm)	M: 2.6" (65 mm)
G: 12.4" (316 mm)	N: 7.5" (190 mm)

