

Ishida AC-4000H Price Computing Hanging Scale/Printer



Approvals



PART #	MODEL	CAPACITY
80317.....	AC-4000H.....	30 lb x 0.01 lb
96900* ...	AC-4000H with RF	30 lb x 0.01 lb

Networking capabilities along with user-friendly operation make the new AC-4000H an ideal supermarket scale for seafood, meat and produce applications. The AC-4000H communicates via Ethernet or internal RF wireless transmission.

This hanging version offers great options for seafood, meat, produce and self service applications.

Applications

- Seafood, meat and produce departments and self service

Standard Features

- Static TCP/IP Ethernet communication
- Two pan styles provided: solid and perforated for drainage
- Stainless steel enclosure designed for easy cleaning
- Dual-sided display
- Internal printer for flexible, efficient label production
- Flash ROM for remote update of application software
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

Options/Accessories

COMMUNICATION

- 65231**ScaleLink Pro, product management software
- 93256.....Internal wireless communication, 802.11b/g
- 94743.....Symbol® access point 5131, 802.11b/g (complete with two antennas, power injector and power cord)

LABEL STOCK

Please refer to the Retail Label section of this catalog for ordering information and case quantity pricing.

**RF is factory installed (includes part no. 93256).*

***License file required for operation. Must supply store name and address at time of order. One license required per location.*

NOTE: Because store designs and applications can vary greatly, mounting hardware must be supplied by the distributor or store. A pole mounting bracket is supplied with each scale.

Symbol® is a registered trademark of Symbol Technologies, Inc.



ScaleLink Pro

Sophisticated product management made simple

- Import ASCII delimited files for seamless integration and continued operation
- Joins individual scales to in-store computer, POS servers, or central hosting computer networks
- Enter and maintain item data, price changes and more

CAPACITY/MINIMUM GRADUATION:

30 lb x 0.01 lb

DISPLAY ITEMS:

Tare: 4 digits
 Unit price: 5 digits
 Weight: 5 digits
 Total: 6 digits

DISPLAY:

Fluorescent display (Upper)
 Dot matrix display (Lower) (256 x 16 dots)

PRINTING SPEED:

3.2" (80mm) per second

PRESET KEYS:

92 one-touch preset keys.
 184 preset keys (Assign two items per key)

MEMORY CAPACITY:

Standard: 2MB

LABEL SIZE:

Label width: 1.5" - 2.5" (38 mm - 64 mm)
 Label length: 1.2" - 9.5" (30 mm - 240 mm)

COMMUNICATION:

TCP/IP 10/100 Base T Ethernet

LABEL ROLL:

Inside diameter: 1.6" (40 mm)
 Outside diameter: 3.9" (100 mm)

WEIGHT:

45 lbs

POWER SUPPLY:

AC100 V / 120 V / 220 V / 240 V, 50/60 Hz

POWER CONSUMPTION:

Standby 50W
 Operation 100W

CLASSIFICATION:

NTEP certified, CC 95-057A6, UL listed

WARRANTY:

1-year limited warranty

DIMENSIONS

A: 16.22" (412 mm)	E: 13.78" (350 mm)
B: 5.98" (152 mm)	F: 10.51" (267 mm)
C: 2.55" (65 mm)	G: 14.05" (357 mm)
D: 13.85" (352 mm)	H: 5.98" (152 mm)
	I: 3.14" (80 mm)

MOUNTING SPECIFICATIONS

Pipe: 1.25" outside diameter

