

Biro Model 1433 Meat Saw

FEATURES:

Base, head, doors, platter, and legs are all stainless for less maintenance which gives a better return on your investment.

SPECIFICATIONS:

MEAT CARRIAGE

Stainless Steel "Easy Flow Carriage". Reduces operator fatigue for better performance.

SWITCH

Guarded watertight magnetic switch with thermal overload protection for lower repair costs.

BEARINGS

Heavy duty taper roller bearings used in upper wheel and lower bearing housings.

DRIVE

Non slip silent V-belt, which ensures a constant blade speed of 3550 feet per minute (1100 meters per minute).

MEAT GAUGE PLATE

Adjustable from 1/16" to 6 1/2", locks in position, can be thrown out of gear, entire assembly removable for cleaning, stainless steel faced.

SAFETY PUSHER PLATE

Included.

BLADE STANDARD

3 teeth per inch, 5/8" wide .022 thick 108" long, 8MM between teeth, 16MM thick, 2743MM long

WHEELS

Removable, 14" cast iron, plated.

WEIGHT

Uncrated 360 lbs. (164kg), approximately.
Crated 425 lbs. (193kg), approximately

CERTIFICATIONS

UL, NSF, USDA

OTHER OPTIONS AVAILABLE AT EXTRA COST

Front Table Extension, Stationary Front Table, Longer Meat Gauge Plates, Cord, Plug, Longer Legs, Scallop Blades. Blade speed adjustments in 500 R.P.M. increments at no additional cost.

DIMENSIONS:

