

Ishida OMNi-3000 Series Fully Automatic Wrapper with Printer

NEW!
Product



OMNi-3000ST
with auto-takeaway



PART #	MODEL	CAPACITY
68663	OMNi-3000	30 lb x 0.01 lb
71383	OMNi-3000S	30 lb x 0.01 lb
71054	OMNi-3000ST with auto-takeaway	30 lb x 0.01 lb

From ergonomic design to high-speed performance, the OMNi-3000 Series offers the latest technology to streamline backroom prepackaging operations. This fully-automatic system weighs, wraps and labels at an industry-leading speed of 30 packages per minute. Eye-catching labels containing nutrition information and safe handling instructions print at speeds up to 85mm per second. With the ability to handle family-pack trays up to 16" wide, the OMNi-3000 Series excels in heavy production backrooms. This versatile wrapper also saves film by automatically switching between two film sizes that accommodate a wide range of tray shapes and sizes.

Designed to enhance production, the OMNi-3000 Series' large touchscreen LCD allows operators to easily access PLU and tray lists. Front film loading minimizes production interruptions. Featuring an extremely small footprint, the wrapper's space-saving design allows it to be placed in the center of a room or in a corner, and wheels provide convenient maneuvering. What's more, the OMNi-3000 Series networks with other 3000 Series scales and communicates with ScaleLink Pro.

Applications

- Food processing
- Supermarket back rooms

Standard Features

- Weigh/wrap/label: 30/minute
Wrap: 35/minute
Label only (fixed price): 46-48/minute
- Handles family-pack trays up to 16" wide
- 9.4" touchscreen Liquid Crystal Display (LCD)
- Automatically switches between two film sizes to accommodate a wide range of tray shapes and sizes
- 144 presets, as well as PLU and tray lists
- Front film loading
- Stores and prints graphics for special instructions, nutrition tables, logos, etc.
- Automatic label positioning
- 90° and 180° label rotation (OMNi-3000S/ST)
- Left to right automatic take away conveyor (OMNi-3000ST)
- Large 9" label roll

Options/Accessories

- 65231*ScaleLink Pro software
- 46943.....Pack-off table, 30" W x 22" D x 38" H
(762mm W x 558mm D x 965mm H)
- 47627.....Mitsubishi film, 500mm x 1,000 m roll
- 46940.....MSCU-3000, master board (1MB)
- 46945.....Rotary bin accumulator tub, adjustable height,
28" dia. x 9" D (711mm dia. x 228mm D)
- 71283.....3' gravity conveyor with support legs
- 71526.....5' gravity conveyor with support legs

LABEL STOCK

- 47746.....Safe handling instructions on top of label,
2.52" x 3.34" (64mm x 85mm)
- 47763.....Safe handling instructions in middle of label,
2.52" x 3.34" (64mm x 85mm)
- 47738.....Two-line w/pre-printed safe handling instructions,
2.52" x 2.32" (64mm x 59mm)

* License file required for operation. Must supply store name and address at time of order. One license required per location.

CAPACITY:

30 lb/0.01 lb 15 lb wrapping capacity

DISPLAY:

9.4" LCD touch screen

POWER SUPPLY:

208V, 220V, 240V (3 phase), standard 20A circuit

POWER CONSUMPTION:

1.4 KW

PRINT SPEED:

3.3"/sec (85mm/sec)

PRESET KEYS:

Preset key: 72 keys (144 using SHIFT key)
Function key: 48 keys

WRAPPING SIZE:

Width: 5.1" - 16.1" (130mm - 410mm)

Length: 5.1" - 10.2" (130mm - 260mm)

Height: 0.8" - 5.9" (20mm - 150mm)

PRINT ITEM:

Item name, unit price, weight, total price, special price, expiration date, pack date, shop address, shop name, message, bar code, ingredients, tare, pack time

CYCLE SPEED:

Weigh/Wrap/Label: 30/minute

Wrap: 35/minute

Label only (fixed price):

46-48/minute

MEMORY:

1 MB

FILM:

Two rolls, automatic film selection

ROLL SIZES:

14" to 24"

LABEL SIZE:

Flexible. Maximum width: 2.52" (64mm)

Maximum length: 4.72" (120mm)

(85mm maximum length for automatic application)

LABEL ROLL:

Maximum diameter: 9.0" (230mm)

HUMIDITY RANGE:

30-80%

RECOMMENDED TEMPERATURE:

50° F to 86° F (10° C to 30° C)

CLASSIFICATION:

NTEP certified, CC# 95-057A5

WARRANTY:

One-year limited warranty

DIMENSIONS

A:* 49.6" (1260mm)	F: 52.3" (1328mm)
B: 49.2" (1250mm)	G: 41.0" (1040mm)
C: 69.3" (1760mm)	H: Outfeed: 43.5" (1105mm)
D: Infeed: 33.7" (856mm)	
E: 35.3" (897mm)	

* Requires 24" on right and left sides for film change

