



Glass Door Merchandiser

VM-2 Model —
Powder Coated Zinc Plated Steel Exterior
Molded ABS Interior

VM-2
VM-2SL



VM-2SL

Standard Features:

- NSF 7 Listed for Foodservice & Prepackaged Products
- Heavy Gauge Black Powder Coated Zinc Plated Steel Exterior
- High Impact Molded ABS Interior
- Bright White Interior with Horizontal Fluorescent Lighting
- Automatic Condensation Disposal
- CFC Free Refrigerant
- Full Height Self-Closing Glass Doors
- Integral Full Length Door Handle
- Bottom Mount Condensing Unit
- Molded-In Shelf Support System Accommodates Standard or Gravity Organizer Shelves without use of Clips or Hooks.
- Eight (8) Standard Shelves
- Shelves Adjustable on 3" Centers
- 9 ft Cord and Plug Attached
- Each VM-2 Shelf will Accommodate
 - One (1) 12" x 20" Pan or
 - One (1) 18" x 26" Pan
- Each VM-2SL Shelf will Accommodate
 - One (1) 12" x 20" Pan

Optional Features:

- Heavy Duty Swivel 3" and 5" Casters with Brakes
- Gravity Organizer Shelves
- Door Merchandising Decals
- Price Tag Molding

The VM-2 and VM-2SL are ideal for merchandising both foodservice and prepackaged products behind full-length display doors.

Cabinet:

The cabinet front, sides, back, and top are constructed of heavy gauge zinc plated steel with a black powder coat finish for optimum durability and corrosion resistance. The interior is made of high impact, low thermal conductive ABS for easy cleaning, exceptional durability, and energy efficiency. Foamed-in-place polyurethane insulation throughout the cabinet ensures the ultimate in energy efficiency. Each VM-2 shelf will accommodate one (1) 12" x 20" pan, or one (1) 18" x 26" pan. Each VM-2SL shelf will accommodate one (1) 12" x 20" pan.

Doors:

The VM-2 self-closing doors have a heavy duty torsion bar to ensure a positive close. The VM-2SL has an adjustable extension spring assembly. The full-size glass provides maximum product visibility.

Refrigeration System:

The self-contained refrigeration system is comprised of a bottom-mounted condensing unit and a forced air cooling coil mounted to the ceiling of the cabinet. The low profile cooling coil nests in a contoured recess in the ABS interior maximizing air circulation. The refrigeration system is designed, tested, and listed with NSF for both foodservice and prepackaged products. Non-electric condensate disposal promotes energy efficiency.





Glass Door Merchandiser

DIMENSIONS

	VM-2	VM-2SL
Width, Overall	52	52
Depth, Overall (incl. handles)	32	31 1/2
Height, Overall (incl. adj. glides)	78	78
Depth, Door Open 90°	56	31 1/2
Clear Door Width	22 1/2	21
Clear Full Door Height	56	55 1/2

CAPACITY

Cubic Feet (net)	43	41
No. of Shelves	8	8
Shelf Area (sq. feet)	29.4	29.4

ELECTRICAL/REFRIGERATION

Voltage	115/60/1
Feed Wires (with Ground)	3
Condensing Unit Voltage	115/60/1
Condensing Unit Size (HP)	1/3
Total Amperes	8.8

CRATED DIMENSIONS & WEIGHT

Height	83
Width	59 1/8
Depth	43
Cubic Feet	122
Weight (lbs.)	520

Dimensional tolerance $\pm 1/4"$ Metric dimensions (MM)

